

• Power Track - Accent Light




90 CRI

PRODUCT HIGHLIGHTS


- Aesthetically designed track mounted vertical-accent luminaire
- 355° rotatable luminaire and 45°-90° adjustable light head
- The complete luminaire is made of extruded aluminium
- High efficient passive cooling extruded aluminium light head
- Aesthetically designed anti glare ABS front ring
- High efficiency vacuum metalized polycarbonate reflector with beam angle options of 12°, 24°, 36° & 60°
- High efficacy chip on board (COB) LED technology
- Inbuilt high efficiency electronic driver technology
- Adaptor-suitable for 3 wire & 4 wire power track
- Shade : powder coated-white, black & grey

Available Colours



White Black Grey

Available Reflector Deg.



IP 20

12°


24°

36°

60°

TECHNICAL SPECIFICATIONS

Light Source	: COB - Chip on Board
Power Consumption	: 15w, 20w, 23w, 27w
Color Temperature	: 3000 K 3500 K 4000 K
Lumens	15w : 1520 lm, 1567 lm, 1574 lm
	20w : 1857 lm, 1890 lm, 1930 lm
	23w : 2160 lm, 2207 lm, 2219 lm
	27w : 2480 lm, 2496 lm, 2529 lm
Driver	: Constant current AC - DC
Input voltage range	: 220 - 240 V
Output voltage	: 33V - 37V DC
Output Current	: 400 mA 500 mA 600 mA 700 mA
Power Factor	: >0.98
THD	: <10%



All dimensions are in mm

Product Application :

Retail Space | Peripheral | Show Window | Wall Display